

LaSpaziale Vivaldi II

The LaSpaziale Vivaldi II is newly released in Australia and offers a extra layer of sophistication over the original Vivaldi S1.

Dual Manometer : It is no longer necessary to purchase a portafilter with a pressure gauge to either check or make adjustments to pump pressure.

New 4 hole steam tip: The four hole steam tip on this machine produces outstanding microfoam.

Decreased delta: The original Vivaldi S1 needs to detect a temperature drop of one degree Celsius before the heater is activated. The new Vivaldi II activates the heater with the detection of a temperature drop of just one half degree Celsius. Simply put, it makes the temperature accuracy that much more precise in the group boiler and enhances the steam boilers performance.

Updated temperature sensing probe: The new probe is actually submerged directly into the boilers. This probe has proven to be more reliable than the previous style and has a quicker reaction time.



New LED display: The previous display showed 5 degree increments, from 85 to 120 degrees Celsius. The NEW Vivaldi II displays in 1 degree increments, from 91 to 97 degrees Celsius.

Available colours: Black, Red (limited) or Grey only

LaSpaziale Vivaldi II Specifications

Boiler capacity	2.5 litre steam 0.45 litre brew
Fresh water tank	Must be plumbed
Voltage	230 v 50 Hz.
Other	Rotary pump, pump and boiler pressure gauges
Watt	Steam 1200 watt. & brew 800 watt
Dimensions (W x D x H)	390 x 420 x 420 mm approx
Weight	Approximately 30 kg
Warranty	All new machines for home use carry a 12 month back to base warranty. Machines for business use carry a 12 month parts and 3 month labour warranty. During this period, the machine is returned to us at the customers cost and we will return it at our cost. Normally we will aim to return the machine within 5 working days.

Exclusions: Misuse, user modified equipment, gaskets and seals and damage caused by scaling.