



SYNESSO

Cyncra & Sabre Specifications

Model	2 Group	3 Group
Voltage, Single Phase	220	220
Hertz	50 / 60	50 / 60
Amps - max draw	28 amp	36 amp
Cord Plug Rating (UL Listed)	30 amp	50 amp
Brew & Steam Specifications:		
Watts per Element, Steam Tank	2000 x 2	2500 x 2
Total Steam Element Wattage	4000	5000
Steam Tank Capacity (Liters)	7.7	12.3
Watts per Element, Brew Tank	700 x 2	700 x 3
Brew Tank Capacities (Liters)	1.9 x 2	1.9 x 3
Machine Dimensions:	Inches / mm	Inches / mm
Height (Steam Wand 21", Handle 20.5")	18" / 457	18" / 457
Width (Steam Handle to Handle add 3")	29" / 736	40" / 1016
Depth	23" / 584	23" / 584
Weights & Dimensions:	Lbs / Kgs	Lbs / Kgs
Machine Weight, Empty	154 / 70	190 / 86
Shipping Weight (approximate)	240 / 109	290 / 131
Boxed Dimensions: L" x W" x H"	42" x 32" x 31"	50" x 32" x 31"
Boxed Dimensions: L x W x H m/m	1042x762x787	1245x813x787
Plumbing (Compression)	3/8" OD	3/8" OD

- Certified by ETL for Sanitation to NSF / ANSI Standard 4
- Certified by ETL for Electrical Safety to ANSI / UL Standard 197
- Certified by ETL for Electrical Safety to CSA Standard C22.2 No. 109
- Certified by KTL for Korean Licensing Standards
- CE Compliant (By request)
- C-Tick Compliant (By request)

